

The background image shows an industrial facility with various pipes, valves, and level gauges. A prominent vertical level gauge is visible on the left, with a scale ranging from 0 to 30 feet. A blue Questtec Magne-Trac level gauge is mounted on a pipe in the upper right. The scene is partially obscured by a teal gradient overlay.

Questtec

SOLUTIONS

MAGNE-TRAC
PRODUCT CATALOG

The New Standard of Level

CONTENTS

SECTION	PAGE
01 A Leader In Liquid Level Measurement	01
02 Magnetic Level Indicator Components	05
03 Safe & Economical Measurement with	10
Magne-Trac Products	
04 Optional Equipment.....	15
05 Accessories: Transmitters & Switches	17
06 Specification Model Guide	23

Represented by:



Zimco Instrumentation Inc.

11141 15 Street NE, Calgary, AB, T3K 0Z5, Canada

Phone: 403-253-8320

Email: info@zimco.ca

Website: www.zimco.ca

1

A LEADER IN

LIQUID LEVEL MEASUREMENT

ABOUT QUESTTEC

Questtec Solutions has a long history of quality, experience, and care in the development and engineering of the liquid level gage and valve product lines.

Over the past fifty years, under the direction of Daniel Measurement and Control, **Questtec Solutions'** products have been consistently refined to remain one of the industry leaders in liquid level measurement. Today, **Questtec Solutions** carries on this legacy with renewed dedication in order to bring you real solutions.

Questtec Solutions, employs over 125 years of collective experience with all aspects of the liquid level gage and valve product lines. With a new state-of-the-art manufacturing facility, and custom weld shop fabrication services, **Questtec Solutions** is able to provide flexibility to tailor to its customer's specific needs.



125+ YEARS

of collective experience in liquid level gage and valve product lines



NEW STATE-OF-THE-ART MANUFACTURING FACILITY



CUSTOM WELD SHOP FABRICATION SERVICES

provide flexibility to tailor to its customer's specific needs

When choosing your liquid level measurement solutions provider, why not choose the best? The symmetry of a field-tested, reputable product, coupled with the energy of new management, has positioned Questtec Solutions to be best suited to assist you in solving your liquid level measurement challenges.

Questtec Solutions delivers engineered solutions to meet the most complex level bridge requirements.

In addition to the existing Daniel Liquid Level Gage and Valve line, this new facility, allows Questtec Solutions to offer new products, which include:



WHY CHOOSE US

At Questtec Solutions, we strive to exceed our customer's expectations by using a hands-on approach.

For every project, we take our customers through a step-by-step process to identify both cost efficient options, as well as, effective solutions for even the most challenging applications. Our approach, high quality products, and experienced team members are testimony to customer confidence in Questtec Solutions as a leader in the liquid level instrumentation industry.

- ☑ ENGINEERED SOLUTIONS
- ☑ FULL-RANGE CAPABILITIES
- ☑ WORLD CLASS MANUFACTURING FACILITY
- ☑ TOP NOTCH WELDING FACILITY



READY TO SPEC? TURN TO "06: SPECIFICATION MODEL GUIDE"



ENGINEERED SOLUTIONS

With collaborative efforts of our dynamic outside sales team and network of domestic and international product representatives, we provide quick insight and responsiveness that customers warrant. In addition, our knowledgeable inside sales team will work alongside production staff to deliver flexible lead times, a variety of options for customized bids, and explore all possible solutions for each individual project.



FULL-RANGE CAPABILITIES

Engineering operations are an essential aspect of developing, adapting, and refining any product line. We offer complete engineering services to all of our customers. From the early development stages of projects, our accomplished engineers will review applications to find efficient solutions. Our approval drawings provide real options for customers' application in regards to applicable code and standards. We recognize that focusing on the engineering of each unit benefits in the assimilation of our products for seamless operations.



WORLD CLASS MANUFACTURING FACILITY

Our manufacturing is split into three distinct skill centers: machining, fabrication, and assembly. All shop work is carefully documented and inspected throughout the manufacturing process. Our production planners follow assigned orders, and communicate job specific requirements to the shop floor. We maintain focus on quality, speed, exceeding customer expectations.

CNC machining and laser engraving capabilities











TOP NOTCH WELDING FACILITY QUALIFICATIONS

Section IX Weld Procedures (WPS)	Procedure Qualifications (PQR)
Welder Certification (Level II Weld Inspector on Staff)	Conforms with PED (Pressure Equipment Directive)
Standard Welds GTAW	MTR (Material Test Reports)
PMI (Positive Material Identification)	Pressure Piping Stamp (PP)
NB-415 Accreditation of R Repair Organizations (R Stamp)	CNC Precision Manufacturing
ASME "S" & "R" and "U, Div. 1" Stamp / ASME B 31.1, B31.3	Over 35 Weld Procedures for numerous material grades

TESTING PROCEDURES

PWHT (Post Weld Heat Treat)	Dye-Penetration (performed in-house)
Radiography	Ultrasonic
Magnetic Particle Testing	Destructive Testing


APPROVALS

 ATEX	 FM	 CSA	 NACE	 CRN	 IEC	 ISO 9001:2008 REGISTERED	 ASME SEC. 1 DIV 1 BPVC CERTIFIED
---	---	--	---	--	--	---	---

APPLICATION OPPORTUNITIES

YOUR SOLUTION FOR LIQUID LEVEL MEASUREMENT

	CHEMICAL & PETROCHEMICAL
	METALS & MINERALS
	REFINING
	OIL & GAS
	POWER GENERATION
	AEROSPACE
	FOOD PROCESSING
	PULP & PAPER



02

MAGNETIC LEVEL INDICATOR COMPONENTS

MAGNETIC LEVEL INDICATOR COMPONENTS

What is a Magnetic Level Indicator, or MLI?

An MLI is a safe and effective way to provide local level indication. With options for non-invasive/externally mounted instrumentation, such as magnetic level switches and transmitters, make the technology a go-to solution for many difficult and demanding applications that require reduced leak points with clear, visible, and reliable level indication. At **Questtec Solutions**, we have built our business on a readiness to adapt to specific customer requirements in terms of customer materials, fabrication, and delivery requirements. Our standard configuration is by no means the limits to our capacity of supply.

A Magnetic Level Indicator (MLI) consists of 5 major components

Constructed of non-magnetic materials including standard 316 SST. Exotic materials such as Alloy 20 & Hastelloy C are available. Traditional inlet & outlet mounted design displaying liquid level to match the vessel level. Complete with flange end closure for accessibility to the float. Magne-Trac chambers are available to ASME 31.1 and 31.3.

FEATURES

Innovative Flag Design Maximizes Magnetic Field

Wide Flags for Enhanced Indicator View

Impact Resistant Polycarbonate Indicator Window

Corrosion Resistant Moving Parts

Wide Variety of Materials

Available to ASME 31.1 / 31.3 Standards



1

INDICATOR

Indicators provide a high-contrast visual representation of the liquid level.


[LEARN MORE, PAGE 9](#)

A chamber is custom-engineered and constructed per the highest manufacturing standards. A wide range of non-magnetic materials such as stainless steel, exotic alloys, and hard plastics are available for construction.


[LEARN MORE, PAGE 12](#)

2

CHAMBER



SCHEDULE 40 CHAMBER CONSTRUCTION AS A STANDARD



3



TRANSMITTER
Loop-powered level transmitters expand the functionality of a magnetic level indicator by providing process data back to the control room. (Magnetostrictive or Guided Wave Radar, as shown.)

LEARN MORE, PAGE 17 & 18

4



SWITCH
Externally mounted magnetic level switches expand control capabilities of MLIs. These can be used as latching level alarms or level controls by sensing the position of the float in the chamber.


LEARN MORE, PAGE 19

5



FLOAT
Engineered and designed to solve each level application, the float is the science behind accurate magnetic level measurement. Size, volume, weight, buoyant force, and construction technique are variables carefully considered before each float is manufactured. Smooth Autogenous welds on all floats producing an ultra-smooth weld, without bead which could interfere with the float's motion.


LEARN MORE, PAGE 8



THE HEART OF THE QUESTTEC FLOAT TECHNOLOGY

Precision Manufactured Float: The magnetic float is the most crucial component within Questtec Solutions' magnetic level indicators.

Constantly pushing the limits of design structure, buoyancy, density, weight and pressure Questtec stays on the cutting edge of innovation. Our engineers aim to provide customers with the most effective solutions no matter how difficult the applications or extreme the environments. Questtec boast solutions for a variety of unique high pressure/high temperature, flashing, interface and corrosive processes.



- 1. STIFFENING RINGS;
- 2. MAGNET;
- 3. FLOAT BODY

CAPABILITIES

Process pressures up to 4,500+ psig [310 bar]¹

Process temperatures up to 800°F [427°C]¹

High temperature magnets to 1000°F [538°C]

Total level specific gravities as low as 0.33¹

Interface float designs available for liquid specific gravity differentials as little as 0.1

Adequate buoyancy to operate effectively and freely in many viscous liquids, including crude oil

¹maximum capabilities can vary depending on combination of pressure, temperature, and media specific gravity

WIDE FLAG INDICATOR DESIGN

Standard indicators consist of anodized aluminum housing; black & yellow rotating flags; and a clear UV scratch resistant polycarbonate window.

Each flag is 1.4" wide to heighten overall viewing capabilities from up to 200ft. The non-corrosive flag materials also eliminate problems with deterioration often encountered with market standard aluminum flag/stainless steel pins. Magne-Trac™ indicators are constructed with a UV scratch resistant polycarbonate window as standard, eliminating the fragility often encountered with glass while still forming a high integrity fit. The tightly sealed housing contains a single column wide flag assembly all aligned within an extruded aluminum case.

SCALE OPTIONS

In addition to the standard stainless steel scale (graduated in feet and inches), other custom scale options are available

Inches only

Offset zero (plus & minus scale divisions)

Negative/Positive (boiler service)


Percent (0 to 100) -10% increment std.

Metric (mm/M)

Volumetric (gallons, liters)

Decimal feet (0.1ft or 0.01ft.divisions)

Given the characteristics of every vessel are different, drawings or strapping tables must be supplied.



EACH FLAG CONTAINS TWO HIGH STRENGTH MAGNETS



200 FEET LEVEL VIEWING



3

SAFE &
ECONOMICAL
MEASUREMENT
WITH MAGNE-TRAC PRODUCTS

QTS

Quest-Tec Solutions
The New Standard of Level

MT-002583 WWW.QTLEVEL.COM
1-866-240-9906

MADE IN U.S.A.
MT-002583
PO# 10990

MAGNETIC LEVEL INDICATOR SPECIFICATION



The Questtec Magne-Trac Engineered to your Specifications!

In applications for extreme pressure, temperature, vibration, and highly corrosive or hazardous material, the Magne-Trac gage will perform where others fail. Features include lower installation costs, easy to read liquid level indication, and low maintenance. The Magne-Trac gage is constructed of non-magnetic materials including standard 316 SST. Exotic materials such as Alloy 20 & Hastelloy C are also available. Traditional inlet & outlet-mounted design display liquid level to match the vessel level. Comes complete with flange end closure for accessibility to float. Magne-Trac chambers are available to ASME 31.1 and 31.3.

FEATURES

Innovative Flag Design Maximizes Magnetic Field	Wide Flags for Enhanced Indicator View
Low Specific Gravities	Corrosion Resistant Moving Parts
Wide Variety of Materials	High Pressure Applications

Available to ASME B31.1/31.3 Standards

SPECIFICATIONS

Measuring Range	Standard single section	12 to 216in
	Multi section (custom)	>216in
Temperature Range	-320°F to 800°F	
Pressure Range	Full Vacuum to 4500 PSIG	
Minimum Specific Gravity	As low as 0.33	

*Consult factory for additional limits/options

MATERIALS OF CONSTRUCTION

Chamber Materials	Standard Alloys	304/304L 316/316L Other 300 series stainless	
	Plastics/ Composites	CPVC PVDF [KYNAR]	
	Exotic Allys	Titanium, Hastelloy-C276, Alloy20	
*NACE Material available on request			
Chamber Diameters	2" Sch 40 [Std]	2-½" Sch 40 or 80	3" Sch 40
Oversized Chamber (Flashing, Boiling & Dirty Service)	3" Sch 40 with smaller OD floats		
Process Connections	Pressure Class Ratings	ANSI 150#; 300#; 600#; 900#; 1500#; 2500#	
	Process Connection	½" to 10+ DN20 to DN150	
	Process Connection Types	MNPT, FNPT, Weldolet®, Sockolet®, Sockweld Flange, Weldneck Flange, Lap Joint Flange; RTJ Flanged, Plain Pipe Stub	

VISUAL INDICATION

Indicator Flags	1.4" Wide Flag Assembly in Yellow/Black (Additional Colors Available on Request)
Indicator Housing	Anodized Aluminum Stainless Steel casing available upon request
Scale Options	Ft./Inches [Std.], Metric, Percentage, Volume, etc. Custom Scales Available

FLOAT SPECIFICATIONS

Float Materials	316/316L, Titanium, Hastelloy-C276, CPVC
Specific Gravity Range	As low as 0.33
Pressure	Up to 4500 PSIG @ 100°F
High Temp Magnets	Up to 1000°F *Selected by Questtec application

TEMPERATURE OPTIONS

High	Insulation Blankets, Electric or Steam Tracing High Temperature Indicators, etc.
Low	Insulation Blankets, Cryogenic Insulation with Non-Frost Extensions, etc.

LEVEL TRANSMITTER & DISCRETE ALARM OPTIONS

Transmitter Options	MTLT-5000 Magnetostrictive Guided Wave Radar (Use Page 22 for GWR Options)
Switch Options	MTLS-1A; MTLS-5A; MTLS-10A; MTLS-PNEU

**MAGNE-TRAC
PLUS
(MTP)**



The Questtec Magne-Trac Plus combines the rugged versatility of the Magne-Trac with the flexibility, accuracy and reliability of a Guided Wave Radar Transmitter inserted into a Bridle-Trac Bypass Chamber.

The two independent level technologies work together to provide reliable level indication and monitoring. The unique design couples the versatility of an MLI and reliability of GWR with minimum vessel penetration and maximum ease of installation with virtually maintenance-free operation.

Change in the process tank level corresponds to change in the Magne-Trac Plus chambers. The float within the chamber actuates flags for visual indication. The instrument mounted within the second chamber also reacts according to the level change.

SPECIFICATIONS

Measuring Range	Standard single section	12 to 216in
	Multi section (custom)	>216in
Temperature Range	-320°F to 800°F	
Pressure Range	Full Vacuum to 4500 PSIG	
Minimum Specific Gravity	As low as 0.33	
Unique Dual Chamber Design	True Independent Level Measurement Devices.	

*Consult factory for additional limits/options

**BRIDLE-TRAC
(BT)
BRIDLE-TRAC
PLUS
(BTP)**



BTP Shown

The Questtec Bridle-Trac is an ideal means of utilizing the power of many technologies without mounting directly into process vessel.

The Questtec Bridle-Trac external chamber is a self-contained cage designed for use with our top mounting level transmitters or switches. Quality construction and a wide selection of configurations make this cage an ideal means of utilizing the power of our many technologies without mounting directly into the process vessel. The chamber is suitable for use with Guided Wave Radar, RF Capacitance Transmitters, Electronic point sensors and top mounted displacer switches. In addition, mount Level Gages and Valves to your Instrument Bridle for ease of maintenance. In addition, the Bridle-Trac Plus allows the utilization of all our other technology offerings such as Magne-Trac, Glass-Trac, Steam-Trac, Armor-Trac and other 3rd party instrumentation with ancillary connections as needed.

SPECIFICATIONS

Sealed or flanged-top chamber options

2", 3" and 4" nominal chamber diameters to accommodate all sensing elements, Schedule 40 pipe as a minimum

Carbon steel or 316 stainless steel materials of construction

Rugged Questtec commercial construction available as well as ASME B31.3, ASME B31.1, NACE or combined NACE and ASME B31.3 construction options

Rated for pressures up to 5000 psi (345 bar)

For applications to 842°F (450°C)

Lengths for measuring ranges to twenty feet (6.1 m)

Broad selection of process connections sizes and types

Head flange bolting included with flange-top models

Suitable for use with RF capacitance transmitters, all electronic point sensors and top mounted displacer switches

Optimal design for use with Guided Wave Radar transmitter:

- Smallest possible chamber diameters
- Temperature rating to match HTHP probe
- Pressure rating to match High Temperature, High Pressure (HTHP) and High Pressure (HP) probes
- Space above and below measuring range to accommodate measurement transition zones

ECO-TRAC
(ET)
ECONOMICAL & SIMPLE



The Questtec Solution Eco-trac series offers the same functionality, robustness, and reliability of our Magne Trac series at more cost efficient design for light industrial services.

This product is safe and very economical alternative to sight glass sight glass technology to reduce leak points and broken glass concerns. The fixed design and specification allow for a quick, cost effective solution to many applications. The EcoTrac series meets and exceeds ASME class 150 ratings in most cases and is ideal for low pressure and temperature applications. Well suited for but not limited to applications such as skid systems, boiler feed water tanks, refrigeration units, wastewater treatment facilities and other light industrial applications. The Eco-Trac series can be combined with our magnetic level transmitters provide continuous level monitoring and magnetic level switches for discrete high and low alarms.

MATERIALS OF CONSTRUCTION

304SS or 316SS Chamber and Flanges

304SS or 316SS Chamber and Carbon Steel Flanges

Chamber/Pipe: 2" sch40

VESSEL CONNECTIONS

M.NPT: ½" to 1", sch80

Flange: ½" to 2" RFSW, sch40

OPERATING CONDITIONS

Min SG	0.65
Max Pressure Rating	500 PSIG
Max Temperature Rating:	300° F
Maximum Length	[Centers/Visible] 220"
Minimum Length	[Centers/Visible] 8"

VISUAL INDICATOR

Aluminum Housing with Polycarbonate Shield	Flags: Black/Yellow	
	No Scale [std.]	Weatherproof

FLOAT

12" long oblong, 316SS [std.]	Titanium
-------------------------------	----------

ACCESSORIES
TRANSMITTERS & SWITCHES



MTLS-1A 1 AMP
MTLS-5A 5 AMP



MTLS-10A
10 AMP



MTLT-5000

**ECO-TRAC
PLUS**
(ETP)



The Eco-Trac Plus series offers the same functionality, robustness and reliability of our Magne-Trac Plus series with a fixed cost-efficient design for light industrial services.

Just like the Eco-Trac series this product is an economical alternative to sight glass technology. The ETP series is combined with the highly reliable guided wave radar harnessing the benefit of two independent technologies in one cost effective solution for visual indication and level monitoring needs. The ETP series also meets and exceeds ASME class 150# ratings and is ideal for low pressure and temperature solution making it well suited for applications such as skid systems, boiler feed water tanks, refrigeration units, wastewater treatment facilities and many other light industrial applications. The ETP series can still be combined with our magnetic level transmitters and switches to provide an even higher level of redundancy.

MATERIALS OF CONSTRUCTION

304SS or 316SS Chamber and Flanges

304SS or 316SS Chamber and Carbon Steel Flanges

Chamber/Pipe: 2" sch40

VESSEL CONNECTIONS

M.NPT: ½" to 1", sch80

Flange: ½" to 2" RFSW, sch40

OPERATING CONDITIONS

Min SG	0.65
Max Pressure Rating	500 PSIG
Max Temperature Rating:	300° F
Maximum Length	[Gliders/Visible] 220"
Minimum Length	[Centers/Visible] 8"

VISUAL INDICATOR

Aluminum Housing with Polycarbonate Shield	Flags: Black/Yellow	Weatherproof
	No Scale	

FLOAT

12" long oblong, 316SS

Titanium

ACCESSORIES
TRANSMITTERS & SWITCHES



MTLS-1A 1 AMP
MTLS-5A 5 AMP



MTLS-10A
10 AMP



MTLT-5000



Guided Wave Radar



1-323-24-108
1" 150# RF 304
SA 182 316SS FLANGE

1-327-01-011
1 1/2" 150# 316SS
RF 182 316SS

PN-1-323-18-108
SIZE: 1" - 150#
RFSW - SCH 40
MAT: 316SS

1-323-15-332P
2" x 1/2" 304 RF 150# SS
SA 182 316SS FLANGE

3-18-620
3/4" 300# RFWN
SS

PN 1-323-15-351P
SIZE: 2" X 3/4" 150# RFSW
SCH 40H
MAT: 316SS

PN 1-323-15-325P
SIZE: 2" X 1/2" 150#
RFSW
MAT: 316SS

1-323-18-622

4

OPTIONAL EQUIPMENT

1-323-15-351P
2" x 3/4" 150# RFSW
SCH 40H

1-327-01-023S
1 1/2" 150# 316SS
RF 182 316SS

PN 1-323-18-164
SIZE: 3/4" 300# RFSW
SCH 40
MAT: 316SS

PN 1-323-15-388P
SIZE: 1 1/2" X 3/4" 300# RF
MAT: 316SS

PN 1-323-15-385P
SIZE: 1" 300# RFWN
SCH 160
MAT: 316SS

PN 1-323-15-385P
SIZE: 1" 300# RFWN
SCH 160
MAT: 316SS

PN-1-323-18-229
1 1/2" 150# 316SS
RF 182 316SS

PN-1-323-18-229

PN-1-323-18-140

1-323-18-704

PN-1-323-18-300P
SIZE: 2" x 1" 300# RFSW
MAT: SA 182 316SS FLANGE

OPTIONAL EQUIPMENT


These items are listed on the Specification Guide for items to add to our MLI.

HIGH-TEMPERATURE INSULATION BLANKET (HB)



Questtec Solutions specializes in custom fiberglass insulation blankets for MLIs of all shapes and sizes. They are constructed with high-quality materials capable of constant contact with temperatures up to 1,000° F [538° C]. This insulation is available as personal protection or with heat tracing options for freeze protection or process temperature maintenance.

FLASHING DESIGNS (F1 OR F2)



The Flashing design encompasses an oversized chamber with either guide rods (F1) or perforated tube (F2) to allow the outgassing to bypass the smaller sized float that is situated towards one side of the chamber ideal for liquids that boil, flash and/or outgas.

The F1-guide rode solution is ideal for shorter indication lengths (<8 ft), aggressive applications and dirty services (small,

suspended particles). The F2-perforated tube design is ideal for long indication lengths (> 8ft) and clean liquids.

Applications:

- Anhydrous Ammonia,
- Carbon Dioxide,
- Liquid Nitrogen,
- Light Hydrocarbons and Pressure-liquified gases (propane, butane, methane...)

HERMETICALLY-SEALED FLAG INDICATOR (HS)



No gaskets: can't leak or fog

Designed to meet needs of chemical wash down, severe environments and offshore industry. Flag indicators are purged with inert gas and permanently sealed in:

- Glass tubing with 100% fused glass end seals to 400° F [204° C] process temperatures

HEAT TRACING: ELECTRIC (EH) & STEAM (ST)



For applications where process freeze protection or temperature maintenance is required, heat tracing will allow the MLI to operate uninterrupted throughout harsh, cold conditions.

Electric Heat Tracing is available in self-regulating, constant wattage, and mineral insulated varieties. Contact the factory for more information.

COLD INSULATION & FROST EXTENSION (CI)



To facilitate operation where the product is kept cold via chillers, refrigerants, and condensers, cryogenic insulation is provided. By insulating the MLI with a specialized cryogenic jacket, process temperatures can be maintained in the liquid state down to -320° F [-195° C].

A frost extension option is available to prevent ice from collecting on the visual indicator, thereby decreasing the visibility. The extension is constructed of durable acrylic plastic and is provided standard with all cryogenic insulation

MAGNETIC PARTICLE TRAP (MP)



Magnetic Particle Traps provide protection for MLIs. The particles are composed mostly of ferrite, often from carbon steel piping. The trap keeps magnetic particles out of float chamber. The Trap fits in line with the process connection. The trap collects the particles which can be cleaned periodically to ensure continued operation of the magnetic level indicator.

5

ACCESSORIES
TRANSMITTERS
& SWITCHES

MAGNETOSTRICTIVE LIQUID LEVEL TRANSMITTER

MTLT-5000



PRINCIPLES OF OPERATION

The MTLT5000-Magnetostrictive M or L Series is based upon the magnetostrictive principle. The sensing tube contains a wire which is pulsed at fixed time intervals. The interaction of the current pulse with the magnetic field created by the magnetic float causes a torsion stress wave to be induced in the wire. This torsion propagates along the wire at a known velocity from the position of the magnetic float and toward both ends of the wire. The microprocessor-based electronics measure the elapsed time between the start and return pulses and convert it into a 4-20 mA DC output which is proportional to the level being measured.

FEATURES

High Accuracy	4/20mA Analog with HART
AMS Aware	Two Channel Output
Explosion Proof and/or Intrinsically Safe	No scheduled Maintenance or Recalibration (due to non-contact design of sensing element)
Designed and Tested with Questtec Magne-Trac Series	

SPECIFICATIONS

LEVEL OUTPUT

Full Range	.5 ft. to 25 ft.
Non-Linearity	.035% of Full Scale
Repeatability	.01% of Full Scale or 0.015in [0.381]*
Operating Temperature	Electronics: -40°F [-40C] to 160°F [71C] Sensing Element: -40°F [-40°C] to 257°F [125°C] Process Temperature: -40°F 9-40°C) to 400°F [204°C]
Output: Signal/Protocol	Standard 4-20mA DC, 2 Wire HART
Inherent Accuracy	+,-[.] 0.039in [1mm] 20" [508mm] to 300" [7620mm]

TRANSMITTER LOOP

Input Voltage	10.5-28 VDC
Fail Safe	High (>21.4mA), or Low (<3.8mA)

CALIBRATION

Zero Adjust Range	Anywhere within active length
Span Adjust Range	FS > 6" from zero

FIELD INSTALLATION


Mounting	External mounted with QTS Z-bracket
Wiring	2-wire twisted shielded cable 3/4" FNPT Conduit Opening

ENVIRONMENTAL

Housing Type	NEMA Type 4X Epoxy Coated Cast Aluminum, 316L Stainless Steel
Humidity	0 to 100% humidity, non-condensing

HOUSING OPTIONS/ DIMENSIONS

Single and Dual Cavity	3/4" FNPT Conduit M20 for ATEX/IECEx Version
-------------------------------	---



Safety Approval	FM/CSA: Explosion-Proof Class I, Groups B, C, D Class II, Groups E, F, G Division I, NEMA 4X	FM/CSA: Intrinsically Safe Class I, Groups A, B, C, D Class II, Groups E, F, G Division I, NEMA 4X
------------------------	---	---



GUIDED WAVE RADAR FOR REDUNDANT LEVEL TECHNOLOGY



Endress+Hauser **EH**
VAR PARTNER

The E&H Guided Wave Radar works with high-frequency radar pulses which are guided along a probe.

These top mounted, direct insertion radars measure interface and direct level of liquids and solids, both of high and low pressures and temperatures. GWR technology provides dependable level indication through pulsating high-frequency, microwave energy down the probe within a bypass chamber. A GWR will read the true level of the process, even in the density diverges over time.

PRINCIPLES OF OPERATION

Levelflex works with high-frequency radar pulses which are guided along a probe. As the pulse impacts the medium surface, the characteristic impedance changes and part of the emitted pulse is reflected. The time between pulse launching and receiving is measured and analyzed by the instrument and constitutes a direct measure for the distance between the process connection and the product surface.

ADVANTAGES

Mounts in bridle chamber to the Magne-Trac and provides Redundant Level	No wet calibration required, simple setup without adjustment
Simultaneous acquisition of interface layer and total level of clear and emulsions interface	Not affected by density of the medium
High Measuring accuracy	Models available to meet applications up to 752° at 5800 psi

FMP50

Levelflex FMP50 is the instrument for basic applications in liquids which do not place high demands on temperature and pressure ranges or chemical resistance. Particularly in basic supply or storage applications as well as utility processes FMP50 is the best choice.

FEATURES	
Accuracy	Rod probe: +/- 2 mm [0.08 in] Rope probe: +/- 2 mm [0.08 in]
Process temperature	-20...+80 °C [-4...+176 °F]
Process pressure absolute / max. over-pressure limit	Vacuum...6 bar, [Vacuum...87 psi]
Max. measurement distance	Rod: 4 m [13 ft] Min DK>1.6 Rope: 12 m [40 ft] Min DK>1.6
Main wetted parts	Rod probe: 316L, PPS, Viton Rope probe: 316, PPS, Viton

FMP51

Continuous level measurement of liquids, pastes and slurries but also for interface measurement. The measurement is not affected by changing media, temperature changes, gas blankets or vapors.

FEATURES	
Process connections	Thread or flange
Temperature	-40 to +200°C [-40 to +392°F]
Pressure	-1 to +40bar [-14.5 to +580psi]
Maximum measuring range	Rod 10m [33ft], rope 45m [148ft], coax 6m [20ft]
Accuracy	±2mm [0.08"]
Dielectric Constant	1.6 [Rod probe, Rope probe], 1.4 [Coax probe]
International explosion protection certificates, overfill prevention WHG SIL, marine approval, 5-point linearity protocol	

FMP54

Continuous measurement in liquids under extreme conditions. Excellent for steam boilers, toxic media using gas tight feed-through guarantee. Reliable results in case of gas and steam phases. Reliable in moving surface, foam and changing medias.

FEATURES	
Process connections	Thread or flange
Temperature	-196 to +450°C [-320 to +842°F]
Pressure	Vacuum -1 to +400bar [Vacuum -14.5 to +5,800psi]
Maximum measuring range	Rod 10m [33ft], Rope 45m [148ft], coax 6m [20ft]
Accuracy	Rod ±2mm [0.08"]
Dielectric Constant	1.6 [Rod probe, Rope probe], 1.4 [Coax probe]
International explosion protection certificates, overfill prevention WHG, SIL, marine approval, steam boiler approval, 5-point linearity protocol	

FMP55

Combination of capacitance and guided wave radar measuring principle in one device. The instrument guarantees safe measured value acquisition even in emulsion layers and issues level and interface layer signals simultaneously.

FEATURES	
Process connections	Thread or flange
Temperature	-50 to +200°C [-58 to +392°F]
Pressure	-1 to +40bar [-14.5 to +580psi]
Maximum measuring range	Rod 4m [13t], rope 10m [33ft], coax 6m [20ft]
Accuracy	Rod ±2mm [0.08"]
Dielectric Constant	1.6 [Rod probe, Rope probe], 1.4 [Coax probe]
International explosion protection certificates, overfill prevention WHG, SIL, marine approval	



READY TO SPEC? TURN TO
"07: SPECIFICATION MODEL GUIDE"

SWITCHES

Questtec level switches are hermetically sealed, non-mercury, bi-stable latching switches, which are designed for use with Magne-Trac level gages.

LEVEL SWITCHES

The bias magnet design latches the switch maintaining the contact after the level continues to rise or fall. The switch will change state when the float magnet passes by. The switches are fully adjustable and non-invasive. Level switches are mounted to the Magne-Trac chamber with all 316 Stainless Steel worm gear pipe clamps. Switch points can be changed easily at any time without any interruption to the visual indication or process.

Standard Enclosure is Cast Aluminum Junction box. Optional, Stainless Steel Junction box. Enclosure Rating is FM/CSA. Level Switches are C Clamp mounted on MLI [standard], clamp mounted on MLI with insulation pad and or attached to a switch mount rod.




MTLS-1A
MTLS-5A



MTLS-10A




MTLS-PNEU



All switches field adjustable. Loosen the mounting clamps and position at desired location. Ensure that the switch always remains in close proximity to the internal float.

SWITCH WIRING


MTLS-1A & 5A



Green = Common
Red = NC
Blue = NO

Red [NC] = Closed when float below switch
Blue [NO] = Closed when float above switch

MTLS-10A



A switch mount rod is an available alternative method for mounting the MTLs to an MLI when insulation is present. The rod assembly, which is welded to the MLI chamber, allows the switch to slide along the full length. When the desired position is selected, simply tighten it in place. Consult Factory.

MODEL	Max Volts	Max Current	Max Power	Dead Band	Max Temp	Min Temp	Contacts	Enclosure Classification
MTLS-1A	120 VAC/ 150 VDC	1.0 AMPS	25W	0.50 Inch	302°F [150°C]	-40°F [-40°C]	SPDT	Class 1 Div 1 Groups B, C, D
MTLS-5A	125 /250 VAC	.5.0 AMPS	1200W					
MTLS-10A	110/250VA C [Resistive]	10.1 AMPS	2500W	0.50 inch	248°F [120°C]	-40°F [-40°C]	2 SPDT	Class 1 & 2 Div 1 & 2 Groups B, C, D
	110/220 VDC	0.5/0.25 Amps	55W					
MTLS-PNEU	Not Applicable	N/A	N/A	0.50 Inch	200°F [93°C]	0°F [-17°C]		

**REFINEME®
(IN-TANK)
TRANSMITTER**
MEASURE MORE WITH LESS



The Level Plus® RefineME® liquid level transmitter satisfies the demand for an accurate and robust liquid-level sensor with unsurpassed flexibility to meet most process application conditions.

The RefineME® transmitter provides 3-in-1 measurement using one process opening for product level, interface level, and temperature measurements. Once the transmitter is installed and calibrated there is no requirement for scheduled maintenance or recalibration. Set it and forget it!



ELECTRONICS

Input Voltage	10.5 to 28 Vdc
Fail Safe	High, Full scale (Modbus, DDA) Low, 3.5 mA default or High, 22.8 mA (Analog, HART®)
Rev. Polarity Protection	Series diode

MOUNTING

Flexible Hose	1 in. Adjustable MNPT or BSPP fitting, Flange mount
---------------	---


WIRING

Connections	4-wire shielded cable or twisted pair, Daniel Woodhead 6-pin male connector, 4570 mm [180 in.] Integral cable with pigtail
-------------	--

ELECTRICAL CONNECTIONS

Single & Dual Cavity	¾ in. FNPT conduit opening, M20 for ATEX/IECEx version
NEMA Type 4X	½ in. FNPT conduit opening Low, 3.5 mA default or High, 22.8 mA (Analog, HART®)

* Whichever is greater | Δ Contact factory for longer lengths. |
◇ Contact factory for specific temperature ranges.



Product Level
Interface Level
Temperature

3-IN-1 MEASUREMENT

FEATURES

3-in-1 Measurement: Product, Interface, Temperature	No Scheduled Maintenance or Recalibration
Inherent Accuracy ±1mm	Integral Display
Intrinsically Safe	API Temperature Corrected Volumes

APPLICATIONS

Inventory Control	Bulk Storage	Custody Transfer
-------------------	--------------	------------------

MARKETS

Petroleum and Petrochemical	LPG terminals	Mining
-----------------------------	---------------	--------

LEVEL OUTPUT

Measured Variable	Product level and interface level
Output signal /Protocol	Modbus RTU, DDA, Analog [4-20 mA], HART®
Order length	Rigid Pipe: 305mm [12in] to 7620mm [300in]
Inherent Accuracy	±1 mm [0.039 in.]
Repeatability	0.001% F.S. or 0.381 mm [0.015 in.] * [any direction]

TEMPERATURE OUTPUT

Measured Variable	Average and multi-point temperatures (Modbus, DDA) Single point temperature (Analog, HART®)
Temperature Accuracy (Modbus, DDA)	±0.2 °C [0.4 °F] range -40 °C [-40 °F] to -20 °C [-4 °F], ±0.1 °C [0.2 °F] range -20 °C [-4 °F] to 70 °C [158 °F], ±0.15 °C [0.3 °F] range 70 °C [158 °F] to 100 °C [212 °F], ±0.5 °C [0.9 °F] range 100 °C [212 °F] to 105 °C [221 °F]
Temperature Accuracy (Analog, HART®)	±0.28 °C [0.5 °F] range -40 °C [-40 °F] to 105 °C [221 °F]

ENVIRONMENTAL

Enclosure Rating	NEMA Type 4X, IP65
Humidity	0 to 100% relative humidity, non-condensing
Operating Temperatures	Electronics: -40 °C [-40 °F] to 71 °C [160 °F] Sensing element: -40 °C [-40 °F] to 125 °C [257 °F] ◇ Temperature element: -40 °C [-40 °F] to 105 °C [221 °F]
Vessel Pressure	Rigid Pipe: 2000psi [138 bar]
Materials	Wetted parts: 316L stainless steel † Non-wetted parts: 316L stainless steel, Epoxy coated aluminum

DISPLAY

Measured Variables	Product level, interface level and temperature
--------------------	--

TANK SLAYER® (IN-TANK) TRANSMITTER

MEASURE MORE
WITH LESS



The Level Plus® Tank Slayer® liquid level transmitter satisfies the demand for an accurate and robust liquid-level sensor with unsurpassed flexibility to meet most process conditions.

The Tank Slayer® transmitter provides 3-in-1 measurement using one process opening for product level, interface level, and temperature measurements. Once the transmitter is installed and calibrated there is no requirement for scheduled maintenance or recalibration. **Set it and forget it!**

FEATURES

3-in-1 Measurement: Product, Interface, Temperature	No Scheduled Maintenance or Recalibration
Inherent Accuracy ±1mm	Integral Display
Intrinsically Safe & Hazardous Area Certified	API Temperature Corrected Volumes

APPLICATIONS

Inventory Control	Bulk Storage	Custody Transfer
-------------------	--------------	------------------

MARKETS

Petroleum and Petrochemical	LPG terminals	Mining
-----------------------------	---------------	--------

LEVEL OUTPUT

Measured Variable	Product level and interface level
Output signal /Protocol	Modbus RTU, DDA, Analog [4-20 mA], HART®
Order length	Flexible hose: 1575 mm [62 in.] to 22000 mm [866 in.] Δ§
Inherent Accuracy	±1 mm [0.039 in.]
Repeatability	0.001% F.S. or 0.381 mm [0.015 in.]* [any direction]

TEMPERATURE OUTPUT

Measured Variable	Average and multi-point temperatures [Modbus, DDA] Single point temperature [Analog, HART®]
Temperature Accuracy [Modbus, DDA]	±0.2 °C [0.4 °F] range -40 °C [-40 °F] to -20 °C [-4 °F], ±0.1 °C [0.2 °F] range -20 °C [-4 °F] to 70 °C [158 °F], ±0.15 °C [0.3 °F] range 70 °C [158 °F] to 100 °C [212 °F], ±0.5 °C [0.9 °F] range 100 °C [212 °F] to 105 °C [221 °F]
Temperature Accuracy [Analog, HART®]	±0.28 °C [0.5 °F] range -40 °C [-40 °F] to 105 °C [221 °F]

ENVIRONMENTAL

Enclosure Rating	NEMA Type 4X, IP65
Humidity	0 to 100% relative humidity, non-condensing
Operating Temperatures	Electronics: -40 °C [-40 °F] to 71 °C [160 °F] Sensing element: -40 °C [-40 °F] to 125 °C [257 °F] ◊ Temperature element: -40 °C [-40 °F] to 105 °C [221 °F]
Vessel Pressure	Flexible Hose: 260 psi [18 bar]
Materials	Wetted parts: 316L stainless steel † Non-wetted parts: 316L stainless steel, Epoxy coated aluminum

DISPLAY

Measured Variables	Product level, interface level and temperature
--------------------	--

ELECTRONICS

Input Voltage	10.5 to 28 Vdc
Fail Safe	High, Full scale [Modbus, DDA] Low, 3.5 mA default or High, 22.8 mA [Analog, HART®]
Rev. Polarity Protection	Series diode

MOUNTING

Flexible Hose	1 in. Adjustable MNPT or BSPP fitting, Flange mount
---------------	--


WIRING

Connections	4-wire shielded cable or twisted pair, Daniel Woodhead 6-pin male connector, 4570 mm [180 in.] Integral cable with pigtail
-------------	--

ELECTRICAL CONNECTIONS

Single & Dual Cavity	¾ in. FNPT conduit opening, M20 for ATEX/IECEx version
NEMA Type 4X	½ in. FNPT conduit opening Low, 3.5 mA default or High, 22.8 mA [Analog, HART®]

* Whichever is greater | Δ Contact factory for longer lengths. |
◊ Contact factory for specific temperature ranges.



Product Level
Interface Level
Temperature


3-IN-1 MEASUREMENT

6


OUR SPECIFICATION &
MODEL CODE GUIDES

TYPICAL TANK CONFIGURATIONS


QUESTTEC SOLUTIONS




STYLE A




STYLE B




STYLE C



STYLE D




STYLE H



INTERFACE

BRIDLE-TRAC (BT)



The **Questtec Solutions** Bridle-Trac utilizes a pipe chamber mounted directly to a vessel with two or more process connections. These connections act as an inlet and outlet that allow the liquid level in the pipe chamber to match the level in the process vessel. A Bridle-Trac may be referred to in the industry as a bridge chamber, a stilling well, a bypass chamber, a cage or a standpipe. It may be used with a customer specified radar for level measurement. All standard chambers are manufactured to Questtec's Heavy Duty Design. Requirements to ASMEB31.1, 31.3 and NACE Design is available upon request.



BT												OPTIONS
BRIDLE-TRAC™												
CHAMBER MATERIAL 4S = 304SS Chamber/Flanges 4C = 304SS Chamber/Carbon Flanges 6S = 316SS Chamber/Flanges 6C = 316SS Chamber/Carbon Flanges HC = C276 Chamber/Flanges MN = Monel Chamber/Flanges CS = Customer Specified	VESSEL CONNECTION 04 = 1/2" 06 = 3/4" 08 = 1" 12 = 1-1/2" 16 = 2" 20 = 2-1/2" 24 = 3" CS = Customer Specified	FLANGE CLASS 01 = 150# 03 = 300# 06 = 600# 09 = 900# 15 = 1500# 25 = 2500# XX = None	DESIGN PRESSURE Specify in PSI	DESIGN TEMPERATURE Specify in deg F	CENTERS Specify in Inches Max Length Single Piece: 264.00", else 2-piece design	INSTRUMENT FOR BRIDLE Z = None Gx = Guided Wave Radar T1 = Other Technology, details required	PLUS EQUIPMENT (BTP)* AT = Armor-Trac ET = Eco-Trac MT = Magne-Trac GT = Glass-Trac QST = Steam-Trac STB = Steam-Trac Bi-color T1 = Other Technology, details required <small>* Respective model numbers/ descriptions continued separately</small>					
BRIDLE STYLE* 1 = Flanges Top/Side Connections, NPT Bottom 2 = NPT Top/Bottom, Flange Side Connections 3 = Flange Top, NPT Bottom/Side Connections 4 = NPT Top/Bottom/Side Connections 5 = Flange Top/Bottom/Side Connections 6 = NPT Top, Bottom/Side Connections 7 = Flange Top/Bottom, NPT Side Connections 8 = NPT Top/Side Connections, Flange Bottom <small>* All Flanges are RFSW - Standard</small>	TOP CONNECTION 04 = 1/2" 06 = 3/4" 08 = 1" 12 = 1-1/2" 16 = 2" 20 = 2-1/2" 24 = 3" CS = Customer Specified	CHAMBER SIZE* 16 = 2" 20 = 2-1/2" 24 = 3" 32 = 4" CS = Customer Specified <small>*Schedule selected by pressure/temperature or customer specification</small>	VENT/DRAIN OPTIONS* AA = 1/2" NPT Vent and Drain AX = 1/2" NPT Vent / No Drain XA = No Vent / 1/2" NPT Drain BB = 3/4" NPT Vent and Drain BX = 3/4" NPT Vent / No Drain XB = No Vent / 3/4" NPT Drain CC = 1" NPT Vent and Drain CX = 1" NPT Vent / No Drain XC = No Vent / 1" NPT Drain XX = None <small>*MNPT hex plug included</small>	CHAMBER RJ = Ring Joint SO = Slip-On Flange WN = Weld-neck Flange SL = Stub End/Lap Joint Flange BW = Butt-Weld Tee design for full-bore process connections IV = Inverted Style Chamber SC = Special Coating AS = ASME "S" Stamp AU = ASME "U" Stamp	TEMP CONTROL CI = Cold Insulation EH = Electric Heat Trace* ST = Steam Trace* HB = Insulation Blanket VD = Vent/Drain Valves* IS = Isolation Valves* <small>*Details Required</small>	MATERIAL & CONSTRUCTION REQUIREMENT OPTIONS NM = NACE* [MR0175 or MR0103] B1 = B31.1 Compliant Construction B3 = B31.2 Compliant Construction CRN = Canadian Registration Number* <small>*Details Required</small>						

ECO-TRAC (ET)

This product is safe and very economical alternative to sight glass sight glass technology to reduce leak points and broken glass concerns. The fixed design and specification allow for a quick, cost effective solution to many applications. The EcoTrac series meets and exceeds ASME class 150 ratings in most cases and is ideal for low pressure and temperature applications. Well suited for but not limited to applications such as skid systems, boiler feed water tanks, refrigeration units, wastewater treatment facilities and other light industrial applications. The Eco-Trac series can be combined with our magnetic level transmitters provide continuous level monitoring and magnetic level switches for discrete high and low alarms.



LEVELFLEX FMP51

(G1 — OPTION IN MTP/ETP/BT/BTP)

Levelflex FMP51 for level measurement even under extreme process conditions like high temperature and high pressure in the process industry. FMP51 offers maximum reliability even in case of moved surface and foam or when numerous tank baffles interfere with the measurement. Levelflex FMP51 is used for continuous level measurement of liquids, pastes and slurries but also for interface measurement. The measurement is not affected by changing media, temperature changes, gas blankets or vapors.


FEATURES

Process Connections	Thread or flange
Temperature	-40 to +200°C [-40 to +392°F]
Pressure	-1 to +40bar [-14.5 to +580psi]
Maximum measuring range	Rod 10m [33ft], rope 45m [148ft], coax 6m [20ft]
Accuracy	±2mm [0.08"]
Dielectric Constant	1.6 [Rod probe, Rope probe], 1.4 [Coax probe]

International explosion protection certificates, overfill prevention WHG SIL, marine approval, 5-point linearity protocol



Endress+Hauser 
VAR PARTNER




LEVELFLEX FMP54

(G4 — OPTION IN MTP/ETP/BT/BTP)

Levelflex FMP54 for continuous level measurement in liquids under extreme conditions. The process connection with its ceramic-graphite seal safeguards high temperature and high pressure applications as they occur in steam boilers and toxic media like ammonia. The gas tight feed through guarantees additional safety. Only the gas phase compensation of the FMP54 gives reliable results in case of gas and steam phases. Reliable measurement in case of moving surface and foam or in changing medias.

FEATURES	
Process connections	Thread or flange
Temperature	-196 to +450°C [-320 to +842°F]
Pressure	Vacuum -1 to +400bar [Vacuum -14.5 to +5,800psi]
Maximum measuring range	Rod 10m [33ft], Rope 45m [148ft], coax 6m [20ft]
Accuracy	Rod ±2mm [0.08"]
Dielectric Constant	1.6 (Rod probe, Rope probe), 1.4 [Coax probe]

International explosion protection certificates, overfill prevention WHG, SIL, marine approval, steam boiler approval, 5-point linearity protocol



LEVELFLEX FMP55

(G5 — OPTION IN MTP/ETP/BT/BTP)

Levelflex FMP55 guided radar with SensorFusion offers the worldwide first combination of the capacitance and guided radar measuring principle in one device. The instrument guarantees safe measured value acquisition even in emulsion layers and issues level and interface layer signals simultaneously. This makes the FMP55 Multiparameter the new standard in interface measurement especially in the oil & gas, chemical and petrochemical industry.




Endress+Hauser 
VAR PARTNER

FEATURES

Process connections	Thread or flange
Temperature	-50 to +200°C [-58 to +392°F]
Pressure	-1 to +40bar [-14.5 to +580psi]
Maximum measuring range	Rod 4m [13ft], rope 10m [33ft], coax 6m [20ft]
Accuracy	Rod ±2mm [0.08"]
Dielectric Constant	1.6 (Rod probe, Rope probe), 1.4 (Coax probe)

International explosion protection certificates, overfill prevention WHG, SIL, marine approval




MTLT 5000


(LPC SERIES)

The MTL5000-Magnetostrictive M or L Series is based upon the magnetostrictive principle. The sensing tube contains a wire which is pulsed at fixed time intervals. The interaction of the current pulse with the magnetic field created by the magnetic float and toward both ends of the wire. The microprocessor-based electronics measure the elapsed time between the start and return pulses and convert it into a 4-20 mA DC output which is proportional to the level being measured.

FEATURES	
No maintenance required	Multidrop HART Communications
FM Approved Explosion Proof/IS	NEMA 4x/7 enclosures
Modular design	Adjustable output damping
Up to .001" resolution	2-wire loop powered
RFI/EMI protection	Available up to 300 inches
Process temperature range: -30 to 250°F	Offers a 4/20 mA 2-wire loop powered circuit for continuous level measurement





"OTS STANDARD"



LEVEL PLUS REFINEME® (LPR SERIES)

Designed for process control in industrial environments: The Level Plus RefineME® liquid level transmitter satisfies the demand for an accurate and robust liquid-level sensor with unsurpassed flexibility to meet most process application conditions. The RefineME® transmitter provides 4-in-1 measurement using one process opening for product level, interface level, temperature and volume measurements. Once the transmitter is installed and calibrated there is no requirement for scheduled maintenance or recalibration for the expected 10 year life of the sensor.

- 4-IN-1 Measurement (Product, Interface, Temperature, Volume)
- No scheduled maintenance or recalibration
- Stainless steel, Nickel Alloy C-276, or FEP wetted parts
- Hazardous area certified
- Inherent Accuracy ±1 mm
- Set it and forget it!





TANK SLAYER

(LPT SERIES)

The Level Plus® Tank Slayer® liquid level transmitter satisfies the demand for an accurate and robust liquid-level sensor with unsurpassed flexibility to meet most process conditions. The Tank Slayer® transmitter provides 3-in-1 measurement using one process opening for product level, interface level, and temperature measurements. Once the transmitter is installed and calibrated there is no requirement for scheduled maintenance or recalibration. Set it and forget it!

FEATURES	
No maintenance required	Multidrop HART Communications
FM Approved Explosion Proof/IS	NEMA 4x/7 enclosures
Modular design	Adjustable output damping
Up to .001" resolution	2-wire loop powered
RFI/EMI protection	Available up to 866 inches
Process temperature range: -30	Offers a 4/20 mA 2-wire loop powered circuit for continuous level measurement



3
in.

Questtec is an International Company with Representatives based throughout the world. Our Partners can assist with Commissioning Start Up and Calibration, 24 Hour Service and Repair Support.

866.240.9906

IMMEDIATE HELP VIA-REMOTE MAINTENANCE

Using the remote maintenance service TeamViewer, the Questtec service technician can assist you immediately, check the instrument configuration and perform certain analysis.



QTS

Quest-Tec Solutions
New Standard of Level

WWW.QTSLEVEL.COM
1-866-240-9906





40,000ft² climate controlled

Questtec
SOLUTIONS

Represented by:

ZIMCO
INSTRUMENTATION

Zimco Instrumentation Inc.

11141 15 Street NE, Calgary, AB, T3K 0Z5, Canada

Phone: 403-253-8320

Email: info@zimco.ca

Website: www.zimco.ca